



For CASE Series III
440 / CT
450 / CT
465

Super High-Flow

34 gpm
4,500 psi
89 hhp

Patent Pending

Specifications

Relief Pressure:	4,500 psi
Maximum Flow (forward):	34 gpm*
Theoretical Horsepower:	89 hhp
Flow at Loader & Aux. Hydraulics: (while high flow is operating)	8 gpm*
High Flow Quick Disconnects:	3/4 in
High Pressure Hoses Rating:	5,000 psi

* at rated engine speed

Features

High hydraulic hp provides maximum power and productivity for your high horsepower attachments.

Applies full engine hp to attachments such as planers, snow blowers, brush cutters and land clearing attachments.

Separate auxiliary flow provides 8 gpm for precise control of attachment positioning without interrupting flow from the high-flow circuit.

High pressure/lower flow and the high-flow pilot operated relief valve maximizes efficiency by reducing flow losses and its resulting heat.

Provides 16 gpm at 4,500 psi reverse flow for dislodging debris during normal operation.

* The 440 is single direction only.

3/4 in. quick disconnects reduce flow losses and heat build up.

Order CASE low-flow with part # 4K, 10DC, 10FE
Do Not order CASE part # 10HH

Benefits

Higher hp available to make your Case SSL/CTL the most productive attachment machine on the market today.

Increases power provided to attachments by 33-50%. Increasing the power and productivity means more efficiency and profitability for your customers.

Lower flow losses and improved relief valve reduce heat build up so the unit runs cooler with less down time.

BIC installation provides properly installed and tested units that are ready to send to the job site.

www.burlingtoninstallation.com

sales@burlinst.com

Rev.8 5/09